AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- 1. (canceled)
- 2. (canceled)
- 3. (canceled)
- 4. (currently amended) A vacuum cleaner, comprising:
 - a nozzle assembly having an inlet opening;
 - a canister assembly connected to said nozzle assembly;
- a cyclonic separation chamber having an inlet, a first outlet and a second outlet, said cyclonic separation chamber being carried on one of said nozzle assembly and said canister assembly;
- a dirt collection vessel having a dirty air inlet and a discharge outlet, said dirt collection vessel being carried on one of said nozzle assembly and said canister assembly; and a suction generator carried on one of said nozzle assembly and said canister
- assembly;

wherein said dirty air inlet is in fluid communication with said first outlet and said second outlet bypasses said dirt collection vessel and a discharge conduit is provided in fluid communication with (a) said second outlet. (b) said discharge outlet and (c) an intake of said suction generator.

- 5. (canceled)
- 6. (previously presented) A vacuum cleaner, comprising:
 - a nozzle assembly having an inlet opening;
 - a canister assembly connected to said nozzle assembly;

a cyclonic separation chamber having an inlet, a first outlet and a second outlet, said cyclonic separation chamber being carried on one of said nozzle assembly and said canister assembly;

a dirt collection vessel having a dirty air inlet in fluid communication with said first outlet and a discharge outlet, said dirt collection vessel being carried on one of said nozzle assembly and said canister assembly;

a suction generator carried on one of said nozzle assembly and said canister assembly;

a discharge conduit in fluid communication with (a) said second outlet, (b) said discharge outlet and (c) an intake of said suction generator; and

a flow control valve in said discharge conduit between said second outlet and said discharge outlet.

- 7. (original) The vacuum cleaner of claim 6, wherein said flow control valve is displaceable between a first position wherein said discharge outlet is closed off from said suction generator intake and a second position wherein said second outlet is closed off from said suction generator intake.
 - 8. (original) The vacuum cleaner of claim 7, further including a dust bag held in

Response dated December 3, 2007

Reply to Office Action of October 11, 2007

said dirt collection vessel, said dust bag including an inlet receiving dirty air from said first outlet.

- 9. (original) The vacuum cleaner of claim 8, wherein said dust bag is made from a material porous to air.
- 10. (original) The vacuum cleaner of claim 8, wherein at least a portion of said dust bag and at least a portion of said dirt collection vessel are transparent.
- 11. (currently amended) The vacuum cleaner of claim 5 claim 4 wherein an air filter is provided in said discharge conduit downstream from said second outlet.
- 12. (original) The vacuum cleaner of claim 11, wherein said air filter is upstream of said discharge outlet.
- 13. (original) The vacuum cleaner of claim 4, including a dirt filter over said second outlet.
- 14. (original) The vacuum cleaner of claim 4, wherein said cyclonic separation chamber is substantially cylindrical in shape and includes an end wall and a sidewall, said first outlet being located adjacent said sidewall and said second outlet being located adjacent an axial centerline of said cyclonic separation chamber on said end wall.
 - 15. (original) The vacuum cleaner of claim 14, wherein said first outlet is also in

S.N. 10/802,966 Response dated December 3, 2007 Reply to Office Action of October 11, 2007

said end wall.

- 16. (original) The vacuum cleaner of claim 4 further including an agitator on said nozzle assembly held in said inlet opening.
 - 17. (canceled)
 - 18. (canceled)
 - 19. (previously presented) A vacuum cleaner, comprising:

a housing;

a cyclonic separation chamber carried on said housing, said cyclonic separation chamber including a first inlet, a first outlet and a second outlet;

a dirt cup having a second inlet in fluid communication with said first outlet and a third outlet; and

a suction generator having a third inlet in fluid communication with said second outlet and said third outlet; and

a valve for selectively controlling airflow between (a) said second and third outlets and (b) said third inlet.

20. (canceled)